TILE REDI®
LUXSHOWER™ PAN

MODEL
DR3260LLWPW


(Not to scale)

60” x 32” LST-L Shower Pan


Left Drain


OD: 60” x 32” (1524 mm x 813 mm)
Threshold Height: 2 1/2” (63.5 mm)
Rough Opening: 60 1/4” x 36 1/4” (1530 mm x 820mm)
Shower Pan Weight: 90lbs. (40.82 kg.)

The LuxShower DR3260LLWPW, 2 1/2” low clearance threshold is designed as a bathtub replacement shower pan with a left drain (Right is also available).The option to add an optional factory applied patented membrane system to the shower pan is perfect for eliminating the risk of leakage at the most vulnerable point between the threshold of the shower pan and the flooring that adjoins, allowing the pan to be tied into a tile or flooring system. The non-slip texture meets and exceeds the F462 COF testing while being very easy to clean and the 1” water dams allow any wall system to be securely added. The grid system on the bottom of the pan has designed locations where elastomeric adhesion can be used to secure the pan to the substrate which is an advantage over other brands. LuxShower shower pans carry a 10 year factory warranty when installed in accordance to the LuxShower installation instructions.




Top View Showing Texture





Section B-B




Section A-A


Drain Layout

Center of Drain is 16 1/8 x 8 9/16” from left stud wall.
A 6” core is recommended for drain clearance*

**Check all building and fire codes prior to installation*



Adhesive Locators
On Corners &
Center Locations



Bottom Rib Layout

Home Innovation LAB CERTIFIED™
Certified by:
Home Innovation Lab
(NAHB):ANSI Z124.2

Toll Free: 800.232.6156
Tel: 954.323.0125
Fax: 954.344.8064
techsupport@tileredi.com
www.tileredi.com

2024.09.11

© 2024 TILE REDI USA, LLC